

Gas Pressure Alarm

- Connect to a Pressure Switch or Contact Gauge
- LED display 1, 2, and 4 gases
- Audible alarm
- Visual alarm
- Mute button
- Connection cords for alarm
- Voltage: 110VAC or 220VAC (optional)



SGPA-1-110
Monitors One (1)
Gas



SGPA-2-110
Monitors Two (2)
Gases



SGPA-4-110
Monitors Four (4)
Gases

Header Bars

- Modular design for easy installation and future expansion
- Outlet connections are available in both GENLOK tube fitting and FSR fittings
- Maximum inlet pressure of 3000 psi
- 100% tested to ensure there are no leaks

Materials

- Pipe OD 1/2", 316L seamless stainless steel tubing (BA grade)
- Connector 316
- Diaphragm valve 316L diaphragm, PCTFE seat, 316L body



GSM L-212D-FNT4-TF8-12



GSM R-212D-FNT4-TF8-12

Ordering Information

GSM Series	R Configuration	2 Stations	12 Station Spacing	D - Station Valve Configuration	FNT4 - Inlet Connection	TF8 - Outlet Connection	12 Spacer
GSM: Stainless Steel	R: Right L: Left	2/3/5	12:12" Custom made, please specify	W: None D: Diaphragm valve	FNT4*: 1/4" NPT(F) NT4: 1/4" NPT(M) VM4: 1/4" FSR(M)	FNT4: 1/4" NPT(F) NT8: 1/2" NPT(M) TF8: 1/2" GENLOK VSF8: 1/2" FSR(M)	6: 6" spacer 12: 12" spacer