

**Wall-Mount Brackets**



**GMB-R1**



**GMB-R6**

Model Number	Inlet / Outlet Connection
<b>GMB-R1</b>	R21, R22 Bracket
<b>GMB-R2</b>	R31 Bracket
<b>GMB-R6</b>	R11, R12, R14, R15, R21, R22, R44 Bracket

**Pigtails**

- Designed for use between cylinder and piping system
- Max. Pressure: GFPT and GFPS Series: 3000 psi (206 bar)  
GRPS Series: 4500 psi (310 bar)
- Temp. Range: GFPS and GRPS Series: -325 to 850°F (-200 to 454°F)  
GFPT: -65 to 450°F (-53 to 230°C)
- Oxygen Service: Meets CGA G4.1 Specifications for cleanliness



**GRPS**

GRPS - Series	C330 - Inlet Connections	CV - Options	00 Outlet Connections
<b>GRPS:</b> Stainless Steel Rigid Pigtail	00: 1/4" NPT(F) C330: CGA330 C350: CGA350 C510: CGA510 C540: CGA540 C580: CGA580 C660: CGA660	Blank: None CV: with Check Valve FA: with Flashback Arrestor	00: 1/4" NPT(F) VSF4: 1/4" Female FSR OD4: 1/4" Tube



**GFPT / GFPS**

GFPT Series	24 - Length	C330 - Inlet Connections	CV - Options	00 Outlet Connections
<b>GFPT:</b> Stainless Steel Flexible Pigtail with Teflon Insert	24: 24" 36: 36"	00: 1/4" NPT(F) C330: CGA330 C350: CGA350 C510: CGA510 C540: CGA540 C580: CGA580 C660: CGA660	Blank: None CV: with Check Valve FA: with Flashback Arrestor	00: 1/4" NPT(F)
<b>GFPS:</b> Stainless Steel Flexible Pigtail with Stainless Steel Insert				