

## Gauges



**G20SL**  
Low Mount (LM)



**GR20SL**  
Back Mount (BM)

Series	Specs.	Wetted	Casing	Connection
G20P (LM)		Brass	Nickel-Plated Steel	1/4" NPT
G20SL (LM)		316L	304	1/4" NPT
GR20SL (BM)		316L	316L	1/4" NPT

2", Dual Scale, Lower Mount				
Model Number		Maxium Scale		Entry
Chrome Plated Brass	Stainless Steel	psi/kPa	psi/bar	
G20P-V30	G20SL-V30	-30in.Hg ~ 30 / 200	-30in.Hg ~ 30 / 2	LM
G20P-V60	G20SL-V60	-30in.Hg ~ 60 / 400	-30in.Hg ~ 60 / 4	LM
G20P-V100	G20SL-V100	-30in.Hg ~ 100 / 700	-30in.Hg ~ 100 / 7	LM
G20P-V150	G20SL-V150	-30in.Hg ~ 100 / 1000	-30in.Hg ~ 100 / 10	LM
G20P-V200	G20SL-V200	-30in.Hg ~ 200 / 1400	-30in.Hg ~ 200 / 14	LM
G20P-V300	G20SL-V300	-30in.Hg ~ 300 / 2000	-30in.Hg ~ 300 / 20	LM
G20P-30	G20SL-30	30 / 200	30 / 2	LM
G20P-60	G20SL-60	60 / 400	60 / 4	LM
G20P-100	G20SL-100	100 / 700	100 / 7	LM
G20P-160	G20SL-160	160 / 1100	160 / 11	LM
G20P-200	G20SL-200	200 / 1400	200 / 14	LM
G20P-300	G20SL-300	300 / 2000	300 / 20	LM
G20P-600	G20SL-600	600 / 4000	600 / 40	LM
G20P-1000	G20SL-1000	1000 / 7000	1000 / 70	LM
G20P-1500	G20SL-1500	1500 / 10000	1500 / 100	LM
G20P-2000	G20SL-2000	2000 / 14000	2000 / 140	LM
G20P-3000	G20SL-3000	3000 / 20000	3000 / 200	LM
G20P-4000	G20SL-4000	4000 / 28000	4000 / 280	LM
G20P-6000	G20SL-6000	6000 / 40000	6000 / 400	LM

2", Dual Scale, Back Mount			
Model Number	Maxium Scale		Entry
Stainless Steel	psi/kPa	psi/bar	
GR20SL-V30	-30in.Hg ~ 30 / 200	-30in.Hg ~ 30 / 2	BM
GR20SL-V60	-30in.Hg ~ 60 / 400	-30in.Hg ~ 60 / 4	BM
GR20SL-V100	-30in.Hg ~ 100 / 700	-30in.Hg ~ 100 / 7	BM
GR20SL-V150	-30in.Hg ~ 100 / 1000	-30in.Hg ~ 100 / 10	BM
GR20SL-V200	-30in.Hg ~ 200 / 1400	-30in.Hg ~ 200 / 14	BM
GR20SL-V300	-30in.Hg ~ 300 / 2000	-30in.Hg ~ 300 / 20	BM
GR20SL-30	30 / 200	30 / 2	BM
GR20SL-60	60 / 400	60 / 4	BM
GR20SL-100	100 / 700	100 / 7	BM
GR20SL-160	160 / 1100	160 / 11	BM
GR20SL-200	200 / 1400	200 / 14	BM
GR20SL-300	300 / 2000	300 / 20	BM
GR20SL-600	600 / 4000	600 / 40	BM
GR20SL-1000	1000 / 7000	1000 / 70	BM
GR20SL-1500	1500 / 10000	1500 / 100	BM
GR20SL-2000	2000 / 14000	2000 / 140	BM
GR20SL-3000	3000 / 20000	3000 / 200	BM
GR20SL-4000	4000 / 28000	4000 / 280	BM
GR20SL-6000	6000 / 40000	6000 / 400	BM

## Electronic Contact Gauges



**GA20SL**  
Lower Mount (LM)



**GRA20SL**  
Back Mount (BM)



**GE20SL**  
Lower Mount (LM)



**GRE20SL**  
Back Mount (BM)

- Contact: normally close (no pressure)
- Adjustable between 5 and 80% of the scale range
- Maximum power: 10 watts DC, 12 VA AC
- Maximum switch voltage: 28 V AC/DC
- Wetted area and casing: 316L
- Temperature: -40 to 158°F (-40 to 70°C)
- Connection: 1/4" NPT
- Accuracy: 3-2-3 (2%)
- Potential-free relay

2", Stainless Steel Contact Gauge, PSI/kPa Dual Scale					
Model Number				Maxium Scale	
Twist Cap		Fixed Cap		psi/kPa	psi/bar
Lower Mount	Back Mount	Lower Mount	Back Mount		
GA20SL-100	GRA20SL-100	GE20SL-100	GRE20SL-100	100 / 700	100 / 7
GA20SL-200	GRA20SL-200	GE20SL-200	GRE20SL-200	200 / 1400	200 / 14
GA20SL-300	GRA20SL-300	GE20SL-300	GRE20SL-300	300 / 2000	300 / 20
GA20SL-400	GRA20SL-400	GE20SL-400	GRE20SL-400	400 / 2800	400 / 28
GA20SL-600	GRA20SL-600	GE20SL-600	GRE20SL-600	600 / 4000	600 / 40
GA20SL-1500	GRA20SL-1500	GE20SL-1500	GRE20SL-1500	1500 / 10000	1500 / 100
GA20SL-3000	GRA20SL-3000	GE20SL-3000	GRE20SL-3000	3000 / 20000	3000 / 200
GA20SL-4000	GRA20SL-4000	GE20SL-4000	GRE20SL-4000	4000 / 28000	4000 / 280

Note: Please consult factory on VCR/FSR gauges or psi/bar and psi/kPa dual scale ranges not listed.