

This 2" pressure gauge is ideal for semiconductor processing, high purity gas delivery, purge panel systems and high purity liquid delivery applications.



## Materials

- Bourdon tube: 316L
- Socket: 316L
- Case: 303

## Standard

- ANSI-ASME B40.1 Grade A

## Accuracy

- 2-1-2%

## Ordering Information

Model NO.	Pressure Ranges (psi)**
1/4" FSR(F)*	
GU20SL-30-VSF4	0 ~ 30
GU20SL-60-VSF4	0 ~ 60
GU20SL-100-VSF4	0 ~ 100
GU20SL-200-VSF4	0 ~ 200
GU20SL-300-VSF4	0 ~ 300
GU20SL-600-VSF4	0 ~ 600
GU20SL-1000-VSF4	0 ~ 1000
GU20SL-3000-VSF4	0 ~ 3000
GU20SL-4000-VSF4	0 ~ 4000
GU20SL-V15-VSF4	30 in Hg VAC ~ 15
GU20SL-V30-VSF4	30 in Hg VAC ~ 30
GU20SL-V60-VSF4	30 in Hg VAC ~ 60
GU20SL-V100-VSF4	30 in Hg VAC ~ 100
GU20SL-V200-VSF4	30 in Hg VAC ~ 200

\* FSR - Face Seal Fittings

\*\* All gauges are dual scale