

## Check Valves



Please contact GENTEC® for additional sizes or cracking pressure available

Model	Inlet Connection	Outlet Connection
SS-CV11-TF2-VI-1	1/8" GENLOK	1/8" GENLOK
SS-CV11-NT2-VI-1	1/8" NPT(M)	1/8" NPT(M)
SS-CV11-FNT2-VI-1	1/8" NPT(F)	1/8" NPT(F)
SS-CV11-TF4-VI-1	1/4" GENLOK	1/4" GENLOK
SS-CV11-NT4-TF4-VI-1	1/4" NPT(M)	1/4" GENLOK
SS-CV11-NT4-VI-1	1/4" NPT(M)	1/4" NPT(M)
SS-CV12-FNT4-VI-1	1/4" NPT(F)	1/4" NPT(F)

Material: 316L | Pressure Rating: 3000 psi | Cracking Pressure: 1 psi | Viton® O-rings standard

## Filters



INLINE FILTER

T-TYPE FILTER

Please see "F Series Filters" catalog for more information

Type	Model	Inlet Connection	Outlet Connection
Inline Type	SS-F4-FNT2	1/8" NPT(F)	1/8" NPT(F)
	SS-F4-TF4	1/4" GENLOK	1/4" GENLOK
	SS-F4-NT4	1/4" NPT(M)	1/4" NPT(M)
T-Type	SS-F4T-FNT2	1/8" NPT(F)	1/8" NPT(F)
	SS-F4T-TF4	1/4" GENLOK	1/4" GENLOK
	SS-F4T-NT4	1/4" NPT(M)	1/4" NPT(M)

Material: 316 | Max. Working Pressure: 3000 psi for inline type, 6000 psi for T-type | Washer: 316L | Nominal Pore Size: 0.5-2 microns

## Pressure Switches

- Complements gas alarm systems
- Monitors gas pressure
- Designed to provide signal to alarm systems
- Pressure is adjustable



Anti-explosion Model



Standard Model

Model No.	Pressure Range	Max. Inlet Pressure	Connection	Anti-explosion
GHPS-1	4~50 psi (0.28~3.45 bar)	1000 psi (69 bar)	1/8" NPT(M)	NO
GHPS-2	300~600 psi (21.68~41.37 bar)	2500 psi (172 bar)	1/8" NPT(M)	NO
GHPS-3	100~1500 psi (6.89~103 bar)	8000 psi (552 bar)	1/4" NPT(M)	NO
GHPS-4E	2~25 psi (0.14~1.72 bar)	600 psi (42 bar)	1/4" NPT(F)	YES
GHPS-5E	15~75 psi (1.03~5.17 bar)	600 psi (42 bar)	1/4" NPT(F)	YES
GHPS-6E	50~450 psi (3.45~31.03 bar)	2000 psi (138 bar)	1/4" NPT(F)	YES